Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-30L-INF-XXXXX-X (ALL ON)

Laboratory and Equipment

Test lab	Viso LabSpion - serial: 2007279764 sensor serial: 0690170290 - Test lab
Spectrometer Manufacturer and Model	LabSpion – Type C, horizontal
Measurement serial number	PH-GVA-2026.Jun.03-9299-VO
Measurement date	2026-06-03

Measurement Conditions

Tested c-planes	36 planes – 10.00°
Tested gamma resolution	1.00°
Input Power	128.9 W

Electrical Data

Input Power	128.9 W
Input Voltage	381.5 V DC
Input Current	0.34 A
Power Factor	1.00

Tested Light Source

Product family	FL200-G2
Luminaire configuration	FL200-G2-XXX-RGBW3083-OM-30L-INF-XXXXX-X (ALL ON)
Manufacturer	GVA Lighting, Inc.
Size (width x length x height)	106 mm 0 mm x 430 mm

Main Light Measurement Results

Output – Total Lumen	4178 - 0% / 100%
Efficiency	32.4 lm/W
Peak Intensity	11533
Correlated Color Temperature, CCT	n/a
Color Rendering Index	n/a
Beam Angle (FWHM) | C0/180	31.4°
Beam Angle (FWHM) | C90/270	30.8°
Field Angle (10%) | C0/180	58.8°Unit: 0-100% of peak intensity
Optical Power	17721 mW
Peak Wavelength	453 nm
Dominant Wavelength	539 nm

Polar Light Distribution Diagram
Unit: 0-100% of peak intensity



C0 - C180
C90 - C270
η = 100%

Linear distribution Diagram



Spectral Distribution



Color Temperature

NaN K

Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-30L-INF-XXXXX-X (ALL ON)

Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	4178 lm
Lumen Up% / Down%	0% / 100%
Peak Intensity	11533 cd
Beam Angle (50%-FWHM)	31.1°

EU Ecodesign parameters

Directionality (DLS or NDLS)	DLS
Ecodesign Useful Luminous Flux	4001 lm
Ecodesign Energy Class	G

Intensity Ratio

In 120° cone	98.82%
In 90° cone	95.77%

Angular Distribution





Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-30L-INF-XXXXX-X (ALL ON)

Iso-intensity Diagram (Iso-candela)



90 %	10370.1 cd
80 %	9217.9 cd
70 %	8065.7 cd
60 %	6913.4 cd
50 %	5761.2 cd
40 %	4608.9 cd
30 %	3456.7 cd
20 %	2304.5 cd
10 %	1152.2 cd

Peak intensity: 11522.4 cd
Number of c-planes: 36

Iso-illuminance Diagram (Iso-lux)



50.0 %	640 lx
30.0 %	384 lx
10.0 %	128 lx
5.0 %	64 lx
3.0 %	38.4 lx

Peak illuminance: 1280 lx
Mounting height: 3 m
Number of c-planes: 36

Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-30L-INF-XXXXX-X (ALL ON)

Beam details



Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-30L-INF-XXXXX-X (ALL ON)

Intensity details

Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6	ft
11522	2881	1280	720	461	320	235	180	142	115	95	80	68	59	51	45	40	36	32	29	lux
1070.5	267.6	118.9	66.9	42.8	29.7	21.8	16.7	13.2	10.7	8.8	7.4	6.3	5.5	4.8	4.2	3.7	3.3	3	2.7	fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
11.5k	11.4k	11.1k	10.5k	9.8k	8.9k	7.8k	6.7k	5.6k	4.5k	3.6k	2.8k	2.2k	1.7k	1.4k	1.1k	0.9k	0.7k	0.5k	0.4k	cd
100%	99%	96%	91%	85%	77%	68%	58%	48%	39%	31%	25%	19%	15%	12%	9%	7%	6%	5%	4%	of 0°val

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
11.5k	11.4k	11.1k	10.6k	9.8k	8.8k	7.7k	6.6k	5.4k	4.4k	3.5k	2.8k	2.2k	1.7k	1.4k	1.1k	0.8k	0.7k	0.5k	0.4k	cd
100%	99%	96%	92%	85%	77%	67%	57%	47%	38%	31%	24%	19%	15%	12%	9%	7%	6%	5%	4%	of 0°val

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
11.5k	11.4k	11.1k	10.5k	9.8k	8.9k	7.8k	6.7k	5.6k	4.5k	3.6k	2.8k	2.2k	1.7k	1.4k	1.1k	0.9k	0.7k	0.5k	0.4k	cd
100%	99%	96%	91%	85%	77%	68%	58%	48%	39%	31%	25%	19%	15%	12%	9%	7%	6%	5%	4%	of 0°val

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
11.5k	11.4k	11.1k	10.6k	9.8k	8.8k	7.7k	6.6k	5.4k	4.4k	3.5k	2.8k	2.2k	1.7k	1.4k	1.1k	0.8k	0.7k	0.5k	0.4k	cd
100%	99%	96%	92%	85%	77%	67%	57%	47%	38%	31%	24%	19%	15%	12%	9%	7%	6%	5%	4%	of 0°val

Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-30L-INF-XXXXX-X (ALL ON)

Power details

Input power	
Frequency of input power	0.0 Hz
Power feed to light source	128.9 W
RMS Input voltage feed V,RMS	381.5 V
RMS Input current feed I,RMS	0.34 A
Volt-Amp or apparent power = V,RMS*I,RMS	128.9 VA
Displacement factor of AC power feed	1.00
Power factor of AC current feed	1.00
Total harmonic distortion of the current	0%
Total harmonic distortion of the voltage	0%

Input power curve

Efficiency

Radiated power efficiency	13.74
Lumen efficiency	32.4 lm/W

Stabilization details

Warmup Conditions		Color Temperature Change	
Stable period	15 min	CCT start	n/a
Stable change max	2%	CCT shift	n/a
Minimum time	15 min	CCT end	n/a
Warmup Result		**Output Change**	
Total warmup time	Not completed	Output start	4183 lm
Warmup variation	-0.1416%	Output change	-5.2833 lm
		Output end	4178 lm

Stabilization Curve



Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-30L-INF-XXXXX-X (ALL ON)

IESNA TM-15-07 LUMINIARE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

Forward Light			
Low (0-30°)	1770	lm	42.3%
Medium (30-60°)	299	lm	7.15%
High (60-80°)	24.4	lm	0.583%
Very High (80-90°)	0.313	lm	0.00749%
Back Light			
Low (0-30°)	1770	lm	42.3%
Medium (30-60°)	299	lm	7.15%
High (60-80°)	24.4	lm	0.583%
Very High (80-90°)	0.313	lm	0.00749%
Uplight			
Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%
Total			
Sum	4178	lm	100%

BUG RATING B3 U0 G0