Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-4010-INF-XXXXX-X (R)

Laboratory and Equipment

Test lab	Viso LabSpion - serial: 2007279764 sensor serial: 0690170290 - Test lab
Spectrometer Manufacturer and Model	LabSpion – Type C, horizontal
Measurement serial number	PH-GVA-2026.May.27-8929-VO
Measurement date	2026-05-27

Measurement Conditions

Tested c-planes	36 planes – 10.00°
Tested gamma resolution	0.36°
Input Power	128.9 W

Electrical Data

Input Power	128.9 W
Input Voltage	381.4 V DC
Input Current	0.34 A
Power Factor	1.00

Tested Light Source

Product family	FL200-G2
Luminaire configuration	FL200-G2-XXX-RGBW3083-OM-4010-INF-XXXXX-X (R)
Manufacturer	GVA Lighting, Inc.
Size (width x length x height)	106 mm 0 mm x 430 mm

Main Light Measurement Results

Output – Total Lumen	3596 - 0% / 100%
Efficiency	27.9 lm/W
Peak Intensity	24373
Correlated Color Temperature, CCT	n/a
Color Rendering Index	n/a
Beam Angle (FWHM) | C0/180	7.7°
Beam Angle (FWHM) | C90/270	38.8°
Field Angle (10%) | C0/180	21.1°Unit: 0-100% of peak intensity
Optical Power	18593 mW
Peak Wavelength	633 nm
Dominant Wavelength	622 nm

Polar Light Distribution Diagram
Unit: 0-100% of peak intensity



Linear distribution Diagram



Spectral Distribution



Color Temperature

NaN K

Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-4010-INF-XXXXX-X (R)

Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	3596 lm
Lumen Up% / Down%	0% / 100%
Peak Intensity	24373 cd
Beam Angle (50%-FWHM)	15.8°

EU Ecodesign parameters

Directionality (DLS or NDLS)	DLS
Ecodesign Useful Luminous Flux	3540 lm
Ecodesign Energy Class	G

Intensity Ratio

In 120° cone	99.96%
In 90° cone	98.43%

Angular Distribution





Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-4010-INF-XXXXX-X (R)

Iso-intensity Diagram (Iso-candela)



90 %	21817.2 cd
80 %	19393.0 cd
70 %	16968.9 cd
60 %	14544.8 cd
50 %	12120.6 cd
40 %	9696.5 cd
30 %	7272.4 cd
20 %	4848.3 cd
10 %	2424.1 cd

Peak intensity: 24241.3 cd

Number of c-planes: 36

Iso-illuminance Diagram (Iso-lux)



50.0 %	1346 lx
30.0 %	808 lx
10.0 %	269 lx
5.0 %	135 lx
3.0 %	80.8 lx

Peak illuminance: 2692 lx

Mounting height: 3 m

Number of c-planes: 36

Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-4010-INF-XXXXX-X (R)

Beam details



Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-4010-INF-XXXXX-X (R)

Intensity details

Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6	ft
24145	6036	2683	1509	966	671	493	377	298	241	200	168	143	123	107	94	84	75	67	60	lux
2243.2	560.8	249.2	140.2	89.7	62.3	45.8	35	27.7	22.4	18.5	15.6	13.3	11.4	10	8.8	7.8	6.9	6.2	5.6	fc

Intensities in 0° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
24.1k	23.0k	19.7k	15.5k	11.5k	8.4k	6.2k	4.8k	3.8k	3.2k	2.6k	2.2k	1.9k	1.7k	1.5k	1.3k	1.1k	1.0k	0.8k	0.7k	cd
100%	95%	82%	64%	48%	35%	26%	20%	16%	13%	11%	9%	8%	7%	6%	5%	5%	4%	4%	3%	of 0°val

Intensities in 90° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
24.1k	24.2k	24.2k	24.1k	24.0k	23.8k	23.6k	23.3k	22.9k	22.5k	22.0k	21.4k	20.7k	19.9k	18.8k	17.7k	16.4k	15.1k	13.9k	12.6k	cd
100%	100%	100%	100%	99%	99%	98%	96%	95%	93%	91%	89%	86%	82%	78%	73%	68%	63%	57%	52%	of 0°val

Intensities in 180° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
24.1k	23.0k	19.7k	15.5k	11.5k	8.4k	6.2k	4.8k	3.8k	3.2k	2.6k	2.2k	1.9k	1.7k	1.5k	1.3k	1.1k	1.0k	0.8k	0.7k	cd
100%	95%	82%	64%	48%	35%	26%	20%	16%	13%	11%	9%	8%	7%	6%	5%	5%	4%	4%	3%	of 0°val

Intensities in 270° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
24.1k	24.2k	24.2k	24.1k	24.0k	23.8k	23.6k	23.3k	22.9k	22.5k	22.0k	21.4k	20.7k	19.9k	18.8k	17.7k	16.4k	15.1k	13.9k	12.6k	cd
100%	100%	100%	100%	99%	99%	98%	96%	95%	93%	91%	89%	86%	82%	78%	73%	68%	63%	57%	52%	of 0°val

Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-4010-INF-XXXXX-X (R)

Power details

Input power	
Frequency of input power	0.0 Hz
Power feed to light source	128.9 W
RMS Input voltage feed V,RMS	381.4 V
RMS Input current feed I,RMS	0.34 A
Volt-Amp or apparent power = V,RMS*I,RMS	128.9 VA
Displacement factor of AC power feed	1.00
Power factor of AC current feed	1.00
Total harmonic distortion of the current	0%
Total harmonic distortion of the voltage	0%

Input power curve

Efficiency

Radiated power efficiency	14.42
Lumen efficiency	27.9 lm/W

Stabilization details

Warmup Conditions		Color Temperature Change	
Stable period	15 min	CCT start	n/a
Stable change max	2%	CCT shift	n/a
Minimum time	15 min	CCT end	n/a
Warmup Result		**Output Change**	
Total warmup time	Lamp stabilized in 15 min 0 sec	Output start	3627 lm
Warmup variation	-0.9248%	Output change	-30.799 lm
		Output end	3596 lm

Stabilization Curve



Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-4010-INF-XXXXX-X (R)

IESNA TM-15-07 LUMINIARE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

Forward Light			
Low (0-30°)	1620	lm	45.2%
Medium (30-60°)	173	lm	4.82%
High (60-80°)	0.692	lm	0.0192%
Very High (80-90°)	0	lm	0%
Back Light			
Low (0-30°)	1620	lm	45.2%
Medium (30-60°)	173	lm	4.82%
High (60-80°)	0.692	lm	0.0192%
Very High (80-90°)	0	lm	0%
Uplight			
Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%
Total			
Sum	3596	lm	100%

BUG RATING B3 U0 G0