Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-6030-INF-XXXXX-X (W)

Laboratory and Equipment

Test lab	Viso LabSpion - serial: 2007279764 sensor serial: 0690170290 - Test lab
Spectrometer Manufacturer and Model	LabSpion – Type C, horizontal
Measurement serial number	PH-GVA-2026.Apr.17-7949-VO
Measurement date	2026-04-17

Measurement Conditions

Tested c-planes	36 planes – 10.00°
Tested gamma resolution	1.00°
Input Power	128.9 W

Electrical Data

Input Power	128.9 W
Input Voltage	381.4 V DC
Input Current	0.34 A
Power Factor	1.00

Tested Light Source

Product family	FL200-G2
Luminaire configuration	FL200-G2-XXX-RGBW3083-OM-6030-INF-XXXXX-X (W)
Manufacturer	GVA Lighting, Inc.
Size (width x length x height)	106 mm 0 mm x 430 mm

Main Light Measurement Results

Output – Total Lumen	12575 - 0.0806% / 99.92%
Efficiency	97.55 lm/W
Peak Intensity	18902
Correlated Color Temperature, CCT	n/a
Color Rendering Index	n/a
Beam Angle (FWHM) | C0/180	31.1°
Beam Angle (FWHM) | C90/270	59.6°
Field Angle (10%) | C0/180	60.0°Unit: 0-100% of peak intensity
Optical Power	37644 mW
Peak Wavelength	601 nm
Dominant Wavelength	584 nm

Polar Light Distribution Diagram
Unit: 0-100% of peak intensity



C0 - C180
C90 - C270
η = 100%

Linear distribution Diagram



Spectral Distribution



Color Temperature

3031 K

Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-6030-INF-XXXXX-X (W)

Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	12575 lm
Lumen Up% / Down%	0.0806% / 99.92%
Peak Intensity	18902 cd
Beam Angle (50%-FWHM)	42.4°

EU Ecodesign parameters

Directionality (DLS or NDLS)	DLS
Ecodesign Useful Luminous Flux	10.98 lm
Ecodesign Energy Class	F

Intensity Ratio

In 120° cone	95.53%
In 90° cone	87.31%

Angular Distribution





Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-6030-INF-XXXXX-X (W)

Iso-intensity Diagram (Iso-candela)



90 %	17005.4 cd
80 %	15115.9 cd
70 %	13226.4 cd
60 %	11336.9 cd
50 %	9447.4 cd
40 %	7558.0 cd
30 %	5668.5 cd
20 %	3779.0 cd
10 %	1889.5 cd

Peak intensity: 18894.9 cd
Number of c-planes: 36

Iso-illuminance Diagram (Iso-lux)



50.0 %	1050 lx
30.0 %	630 lx
10.0 %	210 lx
5.0 %	105 lx
3.0 %	63 lx

Peak illuminance: 2099 lx
Mounting height: 3 m
Number of c-planes: 36

Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-6030-INF-XXXXX-X (W)

Beam details

Distance (meter)	1 m	2 m	3 m	4 m	5 m
Distance (feet)	3.3 ft	6.6 ft	9.8 ft	13.1 ft	16.4 ft



Beam width (meter)	0.8 m	1.6 m	2.3 m	3.1 m	3.9 m
Beam width (feet)	2.5 ft	5.1 ft	7.6 ft	10.2 ft	12.7 ft

Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-6030-INF-XXXXX-X (W)

Intensity details

Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6	ft
18895	4724	2099	1181	756	525	386	295	233	189	156	131	112	96	84	74	65	58	52	47	lux
1755.4	438.8	195	109.7	70.2	48.8	35.8	27.4	21.7	17.6	14.5	12.2	10.4	9	7.8	6.9	6.1	5.4	4.9	4.4	fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
18.9k	18.7k	18.0k	17.0k	15.7k	14.1k	12.5k	10.8k	9.1k	7.5k	6.1k	4.8k	3.8k	3.0k	2.4k	1.9k	1.5k	1.3k	1.1k	1.0k	cd
100%	99%	95%	90%	83%	75%	66%	57%	48%	40%	32%	26%	20%	16%	12%	10%	8%	7%	6%	5%	of 0°val

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
18.9k	18.8k	18.6k	18.3k	17.9k	17.4k	16.9k	16.3k	15.7k	14.9k	14.2k	13.3k	12.4k	11.4k	10.4k	9.4k	8.3k	7.3k	6.3k	5.4k	cd
100%	100%	99%	97%	95%	92%	89%	86%	83%	79%	75%	70%	66%	60%	55%	50%	44%	39%	33%	28%	of 0°val

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
18.9k	18.7k	18.0k	17.0k	15.7k	14.1k	12.5k	10.8k	9.1k	7.5k	6.1k	4.8k	3.8k	3.0k	2.4k	1.9k	1.5k	1.3k	1.1k	1.0k	cd
100%	99%	95%	90%	83%	75%	66%	57%	48%	40%	32%	26%	20%	16%	12%	10%	8%	7%	6%	5%	of 0°val

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
18.9k	18.8k	18.6k	18.3k	17.9k	17.4k	16.9k	16.3k	15.7k	14.9k	14.2k	13.3k	12.4k	11.4k	10.4k	9.4k	8.3k	7.3k	6.3k	5.4k	cd
100%	100%	99%	97%	95%	92%	89%	86%	83%	79%	75%	70%	66%	60%	55%	50%	44%	39%	33%	28%	of 0°val

Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-6030-INF-XXXXX-X (W)

Power details

Input power	
Frequency of input power	0.0 Hz
Power feed to light source	128.9 W
RMS Input voltage feed V,RMS	381.4 V
RMS Input current feed I,RMS	0.34 A
Volt-Amp or apparent power = V,RMS*I,RMS	128.9 VA
Displacement factor of AC power feed	1.00
Power factor of AC current feed	1.00
Total harmonic distortion of the current	0%
Total harmonic distortion of the voltage	0%

Input power curve

Efficiency

Radiated power efficiency	29.2
Lumen efficiency	97.55 lm/W

Stabilization details

Warmup Conditions		Color Temperature Change	
Stable period	15 min	CCT start	n/a
Stable change max	2%	CCT shift	n/a
Minimum time	15 min	CCT end	n/a
Warmup Result		**Output Change**	
Total warmup time	Not completed	Output start	12.55 lm
Warmup variation	0.3101%	Output change	28.55 lm
		Output end	12.58 lm

Stabilization Curve



Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-6030-INF-XXXXX-X (W)

IESNA TM-15-07 LUMINIARE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

Forward Light			
Low (0-30°)	4190	lm	33.3%
Medium (30-60°)	1820	lm	14.5%
High (60-80°)	256	lm	2.04%
Very High (80-90°)	20.6	lm	0.164%
Back Light			
Low (0-30°)	4190	lm	33.3%
Medium (30-60°)	1820	lm	14.5%
High (60-80°)	256	lm	2.04%
Very High (80-90°)	20.6	lm	0.164%
Uplight			
Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%
Total			
Sum	12.58	lm	100%

BUG RATING B4 U0 G1