Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-7L-INF-XXXXX-X (R)

Laboratory and Equipment

Test lab	Viso LabSpion - serial: 2007279764 sensor serial: 0690170290 - Test lab
Spectrometer Manufacturer and Model	LabSpion – Type C, horizontal
Measurement serial number	PH-GVA-2026.Mar.17-7364-VO
Measurement date	2026-03-17

Measurement Conditions

Tested c-planes	36 planes – 10.00°
Tested gamma resolution	0.30°
Input Power	0 W

Electrical Data

Input Power	0 W
Input Voltage	117.4 V DC
Input Current	0.00 A
Power Factor	NaN

Tested Light Source

Product family	FL200-G2
Luminaire configuration	FL200-G2-XXX-RGBW3083-OM-7L-INF-XXXXX-X (R)
Manufacturer	GVA Lighting, Inc.
Size (width x length x height)	106 mm 0 mm x 430 mm

Main Light Measurement Results

Output – Total Lumen	2057 - 0% / 100%
Efficiency	∞ lm/W
Peak Intensity	84155
Correlated Color Temperature, CCT	n/a
Color Rendering Index	n/a
Beam Angle (FWHM) | C0/180	7.9°
Beam Angle (FWHM) | C90/270	7.9°
Field Angle (10%) | C0/180	14.6°Unit: 0-100% of peak intensity
Optical Power	14104 mW
Peak Wavelength	642 nm
Dominant Wavelength	626 nm

Polar Light Distribution Diagram
Unit: 0-100% of peak intensity



Linear distribution Diagram



Spectral Distribution



Color Temperature

NaN K

Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-7L-INF-XXXXX-X (R)

Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	2057 lm
Lumen Up% / Down%	0% / 100%
Peak Intensity	84155 cd
Beam Angle (50%-FWHM)	7.9°

EU Ecodesign parameters

Directionality (DLS or NDLS)	DLS
Ecodesign Useful Luminous Flux	2057 lm
Ecodesign Energy Class	A

Intensity Ratio

In 120° cone	100%
In 90° cone	100%

Angular Distribution





Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-7L-INF-XXXXX-X (R)

Iso-intensity Diagram (Iso-candela)



90 %	75739.3 cd
80 %	67323.9 cd
70 %	58908.4 cd
60 %	50492.9 cd
50 %	42077.4 cd
40 %	33661.9 cd
30 %	25246.5 cd
20 %	16831.0 cd
10 %	8415.5 cd

Peak intensity: 84154.8 cd
Number of c-planes: 36

Iso-illuminance Diagram (Iso-lux)



50.0 %	4675 lx
30.0 %	2805 lx
10.0 %	935 lx
5.0 %	468 lx
3.0 %	281 lx

Peak illuminance: 9351 lx
Mounting height: 3 m
Number of c-planes: 36

Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-7L-INF-XXXXX-X (R)

Beam details



Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-7L-INF-XXXXX-X (R)

Intensity details

Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6	ft
84155	21039	9351	5260	3366	2338	1717	1315	1039	842	695	584	498	429	374	329	291	260	233	210	lux
7818.2	1954.6	868.7	488.6	312.7	217.2	159.6	122.2	96.5	78.2	64.6	54.3	46.3	39.9	34.7	30.5	27.1	24.1	21.7	19.5	fc

Intensities in 0° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
84.2k	80.7k	70.8k	56.7k	41.1k	27.1k	16.7k	9.9k	5.9k	3.6k	2.5k	1.8k	1.3k	1.0k	0.8k	0.7k	0.5k	0.4k	0.3k	0.2k	cd
100%	96%	84%	67%	49%	32%	20%	12%	7%	4%	3%	2%	2%	1%	1%	1%	1%	0%	0%	0%	of 0°val

Intensities in 90° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
84.2k	80.7k	70.8k	56.7k	41.1k	27.1k	16.7k	9.9k	5.9k	3.6k	2.5k	1.8k	1.3k	1.0k	0.8k	0.7k	0.5k	0.4k	0.3k	0.2k	cd
100%	96%	84%	67%	49%	32%	20%	12%	7%	4%	3%	2%	2%	1%	1%	1%	1%	0%	0%	0%	of 0°val

Intensities in 180° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
84.2k	80.7k	70.8k	56.7k	41.1k	27.1k	16.7k	9.9k	5.9k	3.6k	2.5k	1.8k	1.3k	1.0k	0.8k	0.7k	0.5k	0.4k	0.3k	0.2k	cd
100%	96%	84%	67%	49%	32%	20%	12%	7%	4%	3%	2%	2%	1%	1%	1%	1%	0%	0%	0%	of 0°val

Intensities in 270° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
84.2k	80.7k	70.8k	56.7k	41.1k	27.1k	16.7k	9.9k	5.9k	3.6k	2.5k	1.8k	1.3k	1.0k	0.8k	0.7k	0.5k	0.4k	0.3k	0.2k	cd
100%	96%	84%	67%	49%	32%	20%	12%	7%	4%	3%	2%	2%	1%	1%	1%	1%	0%	0%	0%	of 0°val

Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-7L-INF-XXXXX-X (R)

Power details

Input power	
Frequency of input power	60.0 Hz
Power feed to light source	0 W
RMS Input voltage feed V,RMS	117.4 V
RMS Input current feed I,RMS	0.00 A
Volt-Amp or apparent power = V,RMS*I,RMS	0.0 VA
Displacement factor of AC power feed	0.71
Power factor of AC current feed	NaN
Total harmonic distortion of the current	NaN%
Total harmonic distortion of the voltage	2.047%

Input power curve

Efficiency

Radiated power efficiency	∞
Lumen efficiency	∞ lm/W

Stabilization details

Warmup Conditions		Color Temperature Change	
Stable period	15 min	CCT start	n/a
Stable change max	2%	CCT shift	n/a
Minimum time	15 min	CCT end	n/a
Warmup Result		**Output Change**	
Total warmup time	Lamp stabilized in 15 min 1 sec	Output start	2087 lm
Warmup variation	-1.5125%	Output change	-29.577 lm
		Output end	2057 lm

Stabilization Curve



Photometric Test Report

FL200-G2-XXX-RGBW3083-OM-7L-INF-XXXXX-X (R)

IESNA TM-15-07 LUMINIARE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

Forward Light			
Low (0-30°)	1030	lm	50.0%
Medium (30-60°)	0.0305	lm	0.00148%
High (60-80°)	0	lm	0%
Very High (80-90°)	0	lm	0%
Back Light			
Low (0-30°)	1030	lm	50.0%
Medium (30-60°)	0.0305	lm	0.00148%
High (60-80°)	0	lm	0%
Very High (80-90°)	0	lm	0%
Uplight			
Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%
Total			
Sum	2057	lm	100%

BUG RATING B3 U0 G0