Photometric Test Report

FL25-G2-XXX-3083-12L-INF-XXXXX-X

Laboratory and Equipment

Test lab	Viso LabSpion - serial: 2007279764 sensor serial: 0690170290 - Test lab
Spectrometer Manufacturer and Model	LabSpion – Type C, horizontal
Measurement serial number	PH-GVA-2026.Apr.28-8193-VO
Measurement date	2026-04-28

Measurement Conditions

Tested c-planes	36 planes – 10.00°
Tested gamma resolution	0.50°
Input Power	28.62 W

Electrical Data

Input Power	28.62 W
Input Voltage	381.6 V DC
Input Current	0.08 A
Power Factor	1.00

Tested Light Source

Product family	FL25-G2
Luminaire configuration	FL25-G2-XXX-3083-12L-INF-XXXXX-X
Manufacturer	GVA Lighting, Inc.
Size (width x length x height)	87 mm 0 mm x 190 mm

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	1784 lm – 0%% / 100%%
Efficiency	62.35 lm/W
Peak Intensity	28862 cd
Correlated Color Temperature, CCT	2943 K
Color Rendering Index	CRI 82.5
Beam Angle (FWHM) | C0/180	12.3°
Beam Angle (FWHM) | C90/270	12.5°
Field Angle (10%) | C0/180	23.1°Unit: 0-100% of peak intensity
Field Angle (10%) | C90/270	23.6°
Optical Power	5341 mW
Peak Wavelength	606 nm
Dominant Wavelength	584 nm

Polar Light Distribution Diagram
Unit: 0-100% of peak intensity



C0 - C180
C90 - C270
η = 100%

Linear distribution Diagram



Spectral Distribution



Color Temperature

2943 K

Photometric Test Report

FL25-G2-XXX-3083-12L-INF-XXXXX-X

Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	1784 lm
Lumen Up% / Down%	0% / 100%
Peak Intensity	28862 cd
Beam Angle (50%-FWHM)	12.4°

EU Ecodesign parameters

Directionality (DLS or NDLS)	DLS
Ecodesign Useful Luminous Flux	1784 lm
Ecodesign Energy Class	G

Intensity Ratio

In 120° cone	100%
In 90° cone	99.99%

Angular Distribution





Photometric Test Report

FL25-G2-XXX-3083-12L-INF-XXXXX-X

Iso-intensity Diagram (Iso-candela)



90 %	25947.9 cd
80 %	23064.8 cd
70 %	20181.7 cd
60 %	17298.6 cd
50 %	14415.5 cd
40 %	11532.4 cd
30 %	8649.3 cd
20 %	5766.2 cd
10 %	2883.1 cd

Peak intensity: 28831.0 cd
Number of c-planes: 36

Iso-illuminance Diagram (Iso-lux)



50.0 %	1602 lx
30.0 %	961 lx
10.0 %	320 lx
5.0 %	160 lx
3.0 %	96.1 lx

Peak illuminance: 3203 lx
Mounting height: 3 m
Number of c-planes: 36

Photometric Test Report

FL25-G2-XXX-3083-12L-INF-XXXXX-X

Color details

Correlated Color Temperature, Target	CCT = 2943 K	MacAdam Steps	SDCM = NaN
Correlated Color Temperature, Measured	CCT = 2943 K	Color deviation from BBL	Duv = -0.0001
Color Rendering Index	CRI 82.5	Color coordinates CIE 1931	(x;y) = (0.4411;0.4052)
Color Rendering Index, R9 (red)	R9 = 2.4	Color coordinate CIEs 1960	(u;v) = (0.2528;0.3483)
Color Rendering TM30-18	Rf 83.5	Color coordinate CIEs 1976	(u';v') = (0.2528;0.5225)
	Rg 98.4	Color Quality Scale	CQS = 81.3

CIE 1931 Chromaticity diagram



Spectral power distribution



CIE 1931 Chromaticity - zoomed



Color Rendering Index per reference color (CIE 1995)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
80.7	89.6	97.1	82.6	81.3	88.5	82.4	57.6	2.4	77.3	83.8	75.6	82.7	98.7	71.4

CIE 1931 Chromaticity - SDCM



TM30-18 Rf-values per hue bin



TM30-18 Rf-values per hue bin

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
79.4	80.1	75.2	83.7	88.0	88.3	80.8	91.2	88.3	87.0	83.9	84.8	87.5	81.2	80.8	78.3

Photometric Test Report

FL25-G2-XXX-3083-12L-INF-XXXXX-X

Color details - ANSI/IES TM-30-18 Color Rendition Report

Color Vector Graphic



Color Distortion Graphic

Gamut Index vs. Fidelity Index

Gamut index (Rg)



Fidelity index (Rf)

Color Rendition by Color Evaluation Sample (CES)



Color evaluation sample CES01 through CES99

Local Color Fidelity (per hue bin)



Hue angle bin (j)

Local Chroma Shift (per hue bin)



Hue angle bin (j)

CIE x	0.4411
CIE y	0.4411
CIE u'	0.2528
CIE v'	0.5225

CIE	**13.3-1995**
Ra	82.5
R9	2.4

Photometric Test Report

FL25-G2-XXX-3083-12L-INF-XXXXX-X

Beam details



Photometric Test Report

FL25-G2-XXX-3083-12L-INF-XXXXX-X

Intensity details

Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6	ft
28831	7208	3203	1802	1153	801	588	450	356	288	238	200	171	147	128	113	100	89	80	72	lux
2678.5	669.6	297.6	167.4	107.1	74.4	54.7	41.9	33.1	26.8	22.1	18.6	15.8	13.7	11.9	10.5	9.3	8.3	7.4	6.7	fc

Intensities in 0° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
28.8k	28.3k	26.8k	24.5k	21.6k	18.3k	15.0k	11.8k	9.0k	6.6k	4.8k	3.5k	2.5k	1.8k	1.4k	1.1k	0.9k	0.7k	0.6k	0.5k	cd
100%	98%	93%	85%	75%	64%	52%	41%	31%	23%	17%	12%	9%	6%	5%	4%	3%	2%	2%	2%	of 0°val

Intensities in 90° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
28.8k	28.3k	26.9k	24.6k	21.7k	18.4k	15.2k	12.0k	9.3k	6.9k	5.1k	3.7k	2.7k	2.0k	1.5k	1.2k	0.9k	0.8k	0.6k	0.5k	cd
100%	98%	93%	85%	75%	64%	53%	42%	32%	24%	18%	13%	9%	7%	5%	4%	3%	3%	2%	2%	of 0°val

Intensities in 180° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
28.8k	28.3k	26.8k	24.5k	21.6k	18.3k	15.0k	11.8k	9.0k	6.6k	4.8k	3.5k	2.5k	1.8k	1.4k	1.1k	0.9k	0.7k	0.6k	0.5k	cd
100%	98%	93%	85%	75%	64%	52%	41%	31%	23%	17%	12%	9%	6%	5%	4%	3%	2%	2%	2%	of 0°val

Intensities in 270° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
28.8k	28.3k	26.9k	24.6k	21.7k	18.4k	15.2k	12.0k	9.3k	6.9k	5.1k	3.7k	2.7k	2.0k	1.5k	1.2k	0.9k	0.8k	0.6k	0.5k	cd
100%	98%	93%	85%	75%	64%	53%	42%	32%	24%	18%	13%	9%	7%	5%	4%	3%	3%	2%	2%	of 0°val

Photometric Test Report

FL25-G2-XXX-3083-12L-INF-XXXXX-X

Power details

Input power	
Frequency of input power	0.0 Hz
Power feed to light source	28.62 W
RMS Input voltage feed V,RMS	381.6 V
RMS Input current feed I,RMS	0.08 A
Volt-Amp or apparent power = V,RMS*I,RMS	28.6 VA
Displacement factor of AC power feed	1.00
Power factor of AC current feed	1.00
Total harmonic distortion of the current	0%
Total harmonic distortion of the voltage	0%

Input power curve

Efficiency

Radiated power efficiency	18.66
Lumen efficiency	62.35 lm/W

Stabilization details

Warmup Conditions		Color Temperature Change	
Stable period	15 min	CCT start	2943 K
Stable change max	2%	CCT shift	0 K
Minimum time	15 min	CCT end	2943 K
Warmup Result		**Output Change**	
Total warmup time	Not completed	Output start	1785 lm
Warmup variation	-0.0783%	Output change	-0.6178 lm
		Output end	1784 lm

Stabilization Curve



Photometric Test Report

FL25-G2-XXX-3083-12L-INF-XXXXX-X

IESNA TM-15-07 LUMINIARE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

Forward Light			
Low (0-30°)	881	lm	49.4%
Medium (30-60°)	11.0	lm	0.617%
High (60-80°)	0	lm	0%
Very High (80-90°)	0	lm	0%
Back Light			
Low (0-30°)	881	lm	49.4%
Medium (30-60°)	11.0	lm	0.617%
High (60-80°)	0	lm	0%
Very High (80-90°)	0	lm	0%
Uplight			
Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%
Total			
Sum	1784	lm	100%

BUG RATING B2 U0 G0