Photometric Test Report

FL25-G2-XXX-3083-7L-INF-XXXXX-X

Laboratory and Equipment

Test lab	Viso LabSpion - serial: 2007279764 sensor serial: 0690170290 - Test lab
Spectrometer Manufacturer and Model	LabSpion – Type C, horizontal
Measurement serial number	PH-GVA-2026.Apr.30-8257-VO
Measurement date	2026-04-30

Measurement Conditions

Tested c-planes	36 planes – 10.00°
Tested gamma resolution	0.40°
Input Power	28.62 W

Electrical Data

Input Power	28.62 W
Input Voltage	381.6 V DC
Input Current	0.08 A
Power Factor	1.00

Tested Light Source

Product family	FL25-G2
Luminaire configuration	FL25-G2-XXX-3083-7L-INF-XXXXX-X
Manufacturer	GVA Lighting, Inc.
Size (width x length x height)	87 mm 0 mm x 190 mm

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	1286 lm – 0%% / 100%%
Efficiency	44.93 lm/W
Peak Intensity	40799 cd
Correlated Color Temperature, CCT	2880 K
Color Rendering Index	CRI 82.4
Beam Angle (FWHM) | C0/180	7.4°
Beam Angle (FWHM) | C90/270	8.1°
Field Angle (10%) | C0/180	16.2°Unit: 0-100% of peak intensity
Field Angle (10%) | C90/270	17.1°
Optical Power	3935 mW
Peak Wavelength	607 nm
Dominant Wavelength	584 nm

Polar Light Distribution Diagram
Unit: 0-100% of peak intensity



C0 - C180
C90 - C270
η = 100%

Linear distribution Diagram



Spectral Distribution



Color Temperature

2880 K

Photometric Test Report

FL25-G2-XXX-3083-7L-INF-XXXXX-X

Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	1286 lm
Lumen Up% / Down%	0% / 100%
Peak Intensity	40799 cd
Beam Angle (50%-FWHM)	7.8°

EU Ecodesign parameters

Directionality (DLS or NDLS)	DLS
Ecodesign Useful Luminous Flux	1286 lm
Ecodesign Energy Class	G

Intensity Ratio

In 120° cone	100%
In 90° cone	100%

Angular Distribution





Photometric Test Report

FL25-G2-XXX-3083-7L-INF-XXXXX-X

Iso-intensity Diagram (Iso-candela)



90 %	36604.7 cd
80 %	32537.5 cd
70 %	28470.3 cd
60 %	24403.1 cd
50 %	20335.9 cd
40 %	16268.7 cd
30 %	12201.6 cd
20 %	8134.4 cd
10 %	4067.2 cd

Peak intensity: 40671.8 cd

Number of c-planes: 36

Iso-illuminance Diagram (Iso-lux)



50.0 %	2260 lx
30.0 %	1356 lx
10.0 %	452 lx
5.0 %	226 lx
3.0 %	136 lx

Peak illuminance: 4519 lx

Mounting height: 3 m

Number of c-planes: 36

Photometric Test Report

FL25-G2-XXX-3083-7L-INF-XXXXX-X

Color details

Correlated Color Temperature, Target	CCT = 2880 K	MacAdam Steps	SDCM = NaN
Correlated Color Temperature, Measured	CCT = 2880 K	Color deviation from BBL	Duv = 0.0004
Color Rendering Index	CRI 82.4	Color coordinates CIE 1931	(x;y) = (0.4467;0.4083)
Color Rendering Index, R9 (red)	R9 = 9.0	Color coordinate CIEs 1960	(u;v) = (0.2550;0.3497)
Color Rendering TM30-18	Rf 84.3	Color coordinate CIEs 1976	(u';v') = (0.2550;0.5245)
	Rg 97.2	Color Quality Scale	CQS = 81.6

CIE 1931 Chromaticity diagram



Spectral power distribution



CIE 1931 Chromaticity - zoomed



Color Rendering Index per reference color (CIE 1995)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
80.5	89.5	96.9	81.2	80.2	87.1	83.7	60.0	9.0	75.9	80.2	70.6	82.4	98.3	72.8

CIE 1931 Chromaticity - SDCM



TM30-18 Rf-values per hue bin



TM30-18 Rf-values per hue bin

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
80.4	80.9	76.2	86.0	90.7	90.6	84.4	91.7	88.9	85.1	81.5	84.8	88.2	81.6	82.8	78.2

Photometric Test Report

FL25-G2-XXX-3083-7L-INF-XXXXX-X

Color details - ANSI/IES TM-30-18 Color Rendition Report

Color Vector Graphic



Color Distortion Graphic

Gamut Index vs. Fidelity Index



Gamut index (Rg)

Fidelity index (Rf)

Color Rendition by Color Evaluation Sample (CES)



Color evaluation sample CES01 through CES99

Local Color Fidelity (per hue bin)



Hue angle bin (j)

Local Chroma Shift (per hue bin)



Hue angle bin (j)

CIE x	0.4467
CIE y	0.4467
CIE u'	0.2550
CIE v'	0.5245

CIE	**13.3-1995**
Ra	82.4
R9	9.0

Photometric Test Report

FL25-G2-XXX-3083-7L-INF-XXXXX-X

Beam details



Photometric Test Report

FL25-G2-XXX-3083-7L-INF-XXXXX-X

Intensity details

Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6	ft
40672	10168	4519	2542	1627	1130	830	635	502	407	336	282	241	208	181	159	141	126	113	102	lux
3778.5	944.6	419.8	236.2	151.1	105	77.1	59	46.6	37.8	31.2	26.2	22.4	19.3	16.8	14.8	13.1	11.7	10.5	9.4	fc

Intensities in 0° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
40.7k	38.4k	32.6k	25.4k	18.5k	12.8k	8.7k	6.0k	4.2k	3.0k	2.3k	1.8k	1.4k	1.1k	0.9k	0.7k	0.6k	0.5k	0.4k	0.3k	cd
100%	94%	80%	62%	45%	32%	21%	15%	10%	7%	6%	4%	3%	3%	2%	2%	1%	1%	1%	1%	of 0°val

Intensities in 90° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
40.7k	38.8k	33.9k	27.4k	20.7k	14.9k	10.4k	7.1k	5.0k	3.5k	2.6k	1.9k	1.5k	1.2k	0.9k	0.7k	0.6k	0.5k	0.4k	0.3k	cd
100%	95%	83%	67%	51%	37%	26%	18%	12%	9%	6%	5%	4%	3%	2%	2%	1%	1%	1%	1%	of 0°val

Intensities in 180° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
40.7k	38.4k	32.6k	25.4k	18.5k	12.8k	8.7k	6.0k	4.2k	3.0k	2.3k	1.8k	1.4k	1.1k	0.9k	0.7k	0.6k	0.5k	0.4k	0.3k	cd
100%	94%	80%	62%	45%	32%	21%	15%	10%	7%	6%	4%	3%	3%	2%	2%	1%	1%	1%	1%	of 0°val

Intensities in 270° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	γ
40.7k	38.8k	33.9k	27.4k	20.7k	14.9k	10.4k	7.1k	5.0k	3.5k	2.6k	1.9k	1.5k	1.2k	0.9k	0.7k	0.6k	0.5k	0.4k	0.3k	cd
100%	95%	83%	67%	51%	37%	26%	18%	12%	9%	6%	5%	4%	3%	2%	2%	1%	1%	1%	1%	of 0°val

Photometric Test Report

FL25-G2-XXX-3083-7L-INF-XXXXX-X

Power details

Input power	
Frequency of input power	0.0 Hz
Power feed to light source	28.62 W
RMS Input voltage feed V,RMS	381.6 V
RMS Input current feed I,RMS	0.08 A
Volt-Amp or apparent power = V,RMS*I,RMS	28.6 VA
Displacement factor of AC power feed	1.00
Power factor of AC current feed	1.00
Total harmonic distortion of the current	0%
Total harmonic distortion of the voltage	0%

Input power curve

Efficiency

Radiated power efficiency	13.75
Lumen efficiency	44.93 lm/W

Stabilization details

Warmup Conditions		Color Temperature Change	
Stable period	15 min	CCT start	2879 K
Stable change max	2%	CCT shift	1 K
Minimum time	15 min	CCT end	2880 K
Warmup Result		**Output Change**	
Total warmup time	Lamp stabilized in	Output start	1292 lm
Warmup variation	-0.5093%	Output change	-5.9855 lm
		Output end	1286 lm

Stabilization Curve



Photometric Test Report

FL25-G2-XXX-3083-7L-INF-XXXXX-X

IESNA TM-15-07 LUMINIARE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

Forward Light			
Low (0-30°)	637	lm	49.6%
Medium (30-60°)	5.52	lm	0.430%
High (60-80°)	0	lm	0%
Very High (80-90°)	0	lm	0%
Back Light			
Low (0-30°)	637	lm	49.6%
Medium (30-60°)	5.52	lm	0.430%
High (60-80°)	0	lm	0%
Very High (80-90°)	0	lm	0%
Uplight			
Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%
Total			
Sum	1286	lm	100%

BUG RATING B2 U0 G0