



PRODUCT INFORMATION

MEASUREMENT SERIAL NUMBER:	PH-GVA-2023.Dec.20-2250-VO
DATE OF MEASUREMENT:	12/20/2023
MANUFACTURER:	GVA LIGHTING, INC.
PRODUCT NAME:	HIGHLIGHTER SERIES, HL-GEN4
SIZE (width x length x height):	23.3 mm x 300 mm x 42 mm
LOT:	GP-5-G/HR-4-L/RO-4-L/U73GY1
PROFILE LEGEND:	DLN – NICHE, DL – CLAMPING, CM – CLEAR MATTE, BM – BLACK MATTE, COVE-F – COVE FIXED, COVE-OD – COVE OUTDOOR, INF – INFINITY 380 V DC. ELV – 48 V DC.
	DLN – NICHE, DL – CLAMPING, F – FLAT, R – ROUND, SW – SATIN WHITE, B – BLACK, (RGBW) – ALL CHANNELS ON, (R) – RED, (G) – GREEN, (B) – BLUE, (W) – WHITE

ANGULAR DISTRIBUTION AT C0/180

ANGULAR DISTRIBUTION AT C90/270




LIGHT OUTPUT DATA

TOTAL LUMEN OUTPUT:	259 lm
EFFICACY:	55 lm/W
PEAK INTENSITY:	157 cd
COLOR RENDERING INDEX (CRI):	0.0
COLOR TEMPERATURE (CCT):	0K
FIDELITY INDEX (TM30Rf):	0.0
GAMUT INDEX (TM30Rg):	0.0

BEAM OUTPUT DATA

BEAM ANGLE (FWHM) C0/180:	60.9°
BEAM ANGLE (FWHM) C90/270:	106.7°
FIELD ANGLE (10%) C0/180:	104.2°
FIELD ANGLE (10%) C90/270:	144.7°
NUMBER OF PLANES MEASURED:	36


ISOCANDELA DIAGRAM



POWER OUTPUT DATA


INPUT POWER:	4.7 W
INPUT VOLTAGE:	380 V DC
INPUT CURRENT:	0.012 A
POWER FACTOR:	1.0
OPTICAL POWER:	0.505 mW
PEAK WAVELENGTH:	524 nm
DOMINANT WAVELENGTH:	531 nm

CIE 1931




SPECTRAL DISTRIBUTION

CIE 1931 ZOOM



x: 0.184
y: 0.731
u: 0.065
v: 0.385
 Δuv :
n/a

BEAM DETAILS



Beam intensity from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
157lx	39lx	17lx	10lx	6lx	4lx	3lx	2lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	0lx	0lx	0lx
14.6fc	3.6fc	1.6fc	0.9fc	0.6fc	0.4fc	0.3fc	0.2fc	0.2fc	0.1fc	0.1fc	0.1fc	0.1fc	0.1fc	0.1fc	0.1fc	0.1fc	0fc	0fc	0fc

Intensity in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
157	154	146	134	120	103	81	55	36	25	18	13	10	7	5	3	2	1	0	0
100%	98%	93%	85%	76%	66%	51%	35%	23%	16%	11%	8%	6%	4%	3%	2%	1%	1%	0%	0%

Intensity in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
157	157	156	153	149	145	138	129	119	106	90	73	54	36	21	11	5	2	0	0
100%	100%	99%	98%	95%	92%	88%	82%	76%	68%	57%	46%	35%	23%	13%	7%	3%	1%	0%	0%

Intensity in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
157	154	146	134	120	103	81	55	36	25	18	13	10	7	5	3	2	1	0	0
100%	98%	93%	85%	76%	66%	51%	35%	23%	16%	11%	8%	6%	4%	3%	2%	1%	1%	0%	0%

Intensity in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
157	157	156	153	149	145	138	129	119	106	90	73	54	36	21	11	5	2	0	0
100%	100%	99%	98%	95%	92%	88%	82%	76%	68%	57%	46%	35%	23%	13%	7%	3%	1%	0%	0%