

Light efficiency:



Light quality:



Color temperature:




Output: 9982 lm

Peak: 47408 cd

Power: 204 W

PF: 1.0



Product name:

FL200-CM-RGBW-IM-20-ELV-SM-WHITE

Date and time:

27-Aug-18 11:41:15 AM

Additional Information:

LED: RGBW

FIXTURE: FL200

FILM: 250274 (20°)


COLOR-AMP: ON

STABILIZED: YES

COLOR (RGBW): WHITE

PERFORMED BY: ABDULLAH QURESHI

Color






CIE 1931

x: 0.312

y: 0.323



Spectra





TM30: 70.4

CRI: 74.1 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
72.4	78.6	78.6	74.1	72.1	68.2	84.1	64.8	-14.9	44.9	68.7	40.5	73.7	87.7	69.6


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
64.8	67.9	65.1	67.0	76.8	88.2	85.5	75.4	71.6	51.9	47.1	71.2	79.3	72.4	66.9	77.2

CQS Q values


Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
83.2	94.4	61.7	50.4	62.2	68.3	76.6	85.5	88.3	72.0	64.3	66.4	70.1	61.6	70.3

CQS: 69.4



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
6621 K	74.1	-14.9	70.4	92.8	69.4	0.312	0.323	0.199	0.310	-0.0027



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
47041lx	11760lx	5227lx	2940lx	1882lx	1307lx	960lx	735lx	581lx	470lx	389lx	327lx	278lx	240lx	209lx	184lx	163lx	145lx	130lx	118lx
4370.2fcd	1092.6fcd	485.6fcd	273.1fcd	174.8fcd	121.4fcd	89.2fcd	68.3fcd	54fcd	43.7fcd	36.1fcd	30.3fcd	25.9fcd	22.3fcd	19.4fcd	17.1fcd	15.1fcd	13.5fcd	12.1fcd	10.9fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
47.0K	46.3K	43.2K	38.4K	32.3K	25.9K	19.8K	14.7K	10.7K	7.8K	5.7K	4.3K	3.3K	2.5K	1.9K	1.5K	1.2K	0.9K	0.7K	0.6K
100%	98%	92%	82%	69%	55%	42%	31%	23%	17%	12%	9%	7%	5%	4%	3%	2%	2%	2%	1%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
47.0K	46.2K	42.9K	37.8K	31.7K	25.2K	19.3K	14.3K	10.6K	7.9K	6.0K	4.6K	3.5K	2.7K	2.1K	1.6K	1.2K	1.0K	0.8K	0.7K
100%	98%	91%	80%	67%	54%	41%	30%	22%	17%	13%	10%	7%	6%	4%	3%	3%	2%	2%	1%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
47.0K	46.3K	43.2K	38.4K	32.3K	25.9K	19.8K	14.7K	10.7K	7.8K	5.7K	4.3K	3.3K	2.5K	1.9K	1.5K	1.2K	0.9K	0.7K	0.6K
100%	98%	92%	82%	69%	55%	42%	31%	23%	17%	12%	9%	7%	5%	4%	3%	2%	2%	2%	1%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
47.0K	46.2K	42.9K	37.8K	31.7K	25.2K	19.3K	14.3K	10.6K	7.9K	6.0K	4.6K	3.5K	2.7K	2.1K	1.6K	1.2K	1.0K	0.8K	0.7K
100%	98%	91%	80%	67%	54%	41%	30%	22%	17%	13%	10%	7%	6%	4%	3%	3%	2%	2%	1%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
21.3°	42.8°	63.8°	89.9%	85.9%